




GTM Micro Capsule Filters

PTFE Membrane

GTM Micro Capsule filters are part of Critical Process Filtration's economical, general service product line that can be used to lower the total cost of filtration from simple to the most complex applications. Produced using the same quality materials and manufacturing excellence as our other product lines, you can be assured of their performance, dependability and scalability. While general service filters are not integrity tested or validated for retention, these highly efficient filters remove large amounts of contaminants early in the process to reduce the load on your expensive downstream filters. They are also useful as stand-alone clarifying or particle removal filters in less critical applications.

GTM Micro Capsule cartridge and capsule filters are configured with a Polytetrafluoroethylene (PTFE) membrane. These filters are compatible with many chemicals and are designed for filtering solvents, non-aqueous liquids, and compressed air and gases. They are well suited for the protection of tank contents in industrial manufacturing operations. Pore sizes range from 0.05 to 5.0 μm .

Critical Process provides unrivaled delivery times, technical consulting before purchasing, and very competitively priced high-performance products. Our comprehensive testing & analysis and validation services support your team whenever they need it. Your process experts partnering with our filtration experts is how we deliver your company's solution right the first time.



GTM Micro Capsule filters are recommended for:

- Compressed Air
- Pressurized Gases
- Solvents
- Tank Vents

Fine Particle Removal

Process Gas & Vent Filters



MICRO CAPSULES – Nominal Dimensions

Body Length: 1.9 in. (4.8 cm)

Overall Length: 2.8 to 3.8 in. (7.1 to 9.7 cm)

Outside Diameter: 2.6 in. (6.6 cm)

Maximum Operating Parameters

CAPSULES	
Liquid Operational Pressure	80 psi at 68 °F (5.52 bard at 20 °C)
Gases Operational Pressure	60 psi at 68 °F (4.14 bar at 20 °C)
Operating Temperature (water)	110 °F at 30 psid (43 °C at 2.07 bard)
Forward Differential Pressure	Liquid - 80 psid at 68 °F (5.52 bard at 20 °C) Gas - 60 psi at 68 °F (4.14 bar at 20 °C)
Reverse Differential Pressure	50 psid at 68 °F (3.45 bard at 20 °C)
Recommended Changeout Pressure	35 psid (2.41 bard)

Sanitization & Sterilization

Autoclave*	250 °F (121 °C), 30 min, 25+ cycles
Chemical Sanitization	Performed using industry standard concentrations of hydrogen peroxide, peracetic acid, sodium hypochlorite and other selected chemicals.

Extractables

GTM Micro Capsule filters typically exhibit low levels of non-volatile residues.

Non-Fiber Releasing

The GTM Micro Capsule filters comply with Title 21 CFR sections 210.3 (b)(6) and 211.72, for non-fiber releasing filters.

FDA and EC Compliance

Materials meet the requirements listed by the FDA as appropriate for use in articles intended for repeated food contact as specified in Title 21 CFR sections 174.5, 177.1500, 177.1520, 177.1630, 177.2440, and 177.2600 as applicable. All materials used to make the filters are listed in European Commission Regulation EU/10/2011, Annex 1.


Filtration Area (Nominal)

Area	0.51 ft ²
	474 cm ²

Construction Materials

Filtration Media	Polytetrafluoroethylene (PTFE) Membrane
Media Support	Polypropylene
End Caps, Center Core, Outer Support Cage, Capsule Housing	Polypropylene
Sealing Method	Thermal Bonding
O-Rings/Gaskets Cartridges only	Buna, Viton® (or FKM), EPDM, Silicone, FEP Encapsulated Silicone, FEP Encapsulated Viton (or FKM)

Flow Rates for GTM Micro Capsules by Pore Size



Flow rates for Micro Capsule filters are per filter. The test fluid is water at ambient temperature. Flows are tested using a Micro capsule filter with ½" Sanitary inlet and outlet ports. Rates will vary based on end configuration of the Micro capsule.

GTM Micro Capsule Filters Ordering Information

All Critical Process filters are configurable to meet customer specifications. Fill in the corresponding codes in the boxes below to build your Part Number.

To consult with one of our technical team members, request a quote or place an order: call (603) 880-4420 Ext. 106, or send an email to sales@criticalprocess.com

Micro Capsule Filters

MIC GTM N 000 -

Pore Size Code	Inlet	Inlet Vent Port	Outlet	Outlet Vent Port	Side Vent O-Ring**
-05 = 0.05 µm	1 = 1/8" Hose Barb	1 = 1/8" Hose Barb	1 = 1/8" Hose Barb	1 = 1/8" Hose Barb	B = Buna
-10 = 0.10 µm	2 = 1/4" Hose Barb	2 = 1/4" Hose Barb	2 = 1/4" Hose Barb	2 = 1/4" Hose Barb	E = EP
-20 = 0.22 µm	3 = 1/2" Hose Barb	3 = 1/2" Hose Barb	3 = 1/2" Hose Barb	3 = 1/2" Hose Barb	S = Silicone
-40 = 0.45 µm	4 = Luer Lock	4 = Luer Lock	3B = 1/2" Hose Barb with Filling Bell	4 = Luer Lock	V = Viton (or FKM)
1-0 = 1.0 µm	5 = 1/2" Sanitary*	6 = 1/4" MNPT	4 = Luer Lock	6 = 1/4" MNPT	K = FFKM
3-0 = 3.0 µm	6 = 1/4" MNPT	7 = Side Bleed Valve	5 = 1/2" Sanitary*	7 = Side Bleed Valve	
5-0 = 5.0 µm			6 = 1/4" MNPT		

*When choosing the Sanitary Inlet/Outlet, the Luer Lock or bleed valve option is required for the Vent Port

** O-Ring is only available on Bleed Valve



One Chestnut Street
Nashua, NH 03060
603.880.4420
FAX: 603.880.4536

CriticalProcess.com

The information contained herein is subject to change without notice. The Critical Process Filtration logo is a trademark of Critical Process Filtration, Inc. Viton is a trademark of DuPont Performance Elastomers L.L.C.
© 2025 Critical Process Filtration, Inc. • All Rights Reserved

Data Sheet GTM Micro DS Rev